




US Type Forged Screw Pin Chain Shackle G210/S210

- Capacities 1/3 to 85 tons.
- Hot dip galvanized or electric galvanized.
- Drop forged, quenched and tempered with alloy pins.
- Working load limit permanently shown on every shackle.
- Max proof load is 2.2 times of the working load limited.
- Min. Breaking strength is 6 times or 4 times of the W.L.L. as requirement.

Nominal Size (in)	W.L.L. (t)	Dimension (in)			Weight (kg/pc)
		A	B	C	
1/4	1/2	0.47	0.31	0.97	0.05
5/16	3/4	0.53	0.38	1.07	0.08
3/8	1	0.66	0.44	1.28	0.13
7/16	1-1/2	0.75	0.50	1.48	0.20
1/2	2	0.81	0.63	1.66	0.27
5/8	3-1/4	1.05	0.88	2.40	0.57
3/4	4-3/4	1.25	0.88	2.40	1.19
7/8	6-1/2	1.44	1	2.86	1.43
1	8-1/2	1.69	1.13	3.24	2.15
1-1/4	9-1/2	1.81	1.25	3.61	3.06
1-1/4	12	2.03	1.38	4.97	4.11
1-3/8	13-1/2	2.25	1.50	4.43	5.28
1-1/2	17	2.38	1.63	4.84	7.23
1-3/4	25	2.88	2	5.78	12.19
2	35	3.25	2.25	6.77	19.19
2-1/2	55	4.13	2.75	8.07	32.27
3	85	5	3.25	8.56	42.50



Screw pin anchor shackle meet the requirements of federal specification RR-C-271D type 1VA, grade A, class 2